

Amendments to the Claims:

1. (Currently Amended) A communications system comprising:
a first host capable of transmitting multiplexed data at a first data transfer rate;
a second host capable of receiving multiplexed data at a second data transfer rate;
a network through which data is transferred from the first host to the second host having a third data transfer rate; and
a data throttle, wherein the data throttle limits the first data transfer rate to a throttle value that is less than or equal to the ~~lesser~~ least one of the first data transfer rate, ~~and~~ the second data transfer rate, and the third data transfer rate, and wherein the throttle value transfer rate is obtained during a communication start-up process.
- 2-3. (Canceled).
4. (Original) The system of Claim 1, wherein the throttle value is a predetermined value.
5. (Original) The system of Claim 1 wherein the first host is further comprised of an applications layer, a sockets layer, a transport layer, and a network layer.
6. (Previously Presented) The system of Claim 5, wherein the data throttle operates by one or more application program interface (API) calls from the applications layer to the sockets layer, said API calls limiting the transmission data rate to the throttle value.

7. (Original) The system of Claim 5, wherein the transport layer is comprised of a User Datagram Protocol (UDP) and the network layer is comprised of an Internet Protocol (IP).

8-11. (Canceled)

12. (Previously Presented) The system of Claim 1, wherein the communications start-up process is a Session Initiation Protocol (SIP) process.

13-15. (Canceled)

16. (Currently Amended) A method comprising:
obtaining a data transfer rate of ~~the~~a first host and a data transfer rate of ~~the~~a second host at which the second host may receive data;

obtaining a data transfer rate of respective one or more intervening packet processing platforms located between the first and second host;

setting, during a communication start-up process, a throttle value that is less than or equal to the ~~lesser~~least of the data transfer rate of the first host, ~~and~~ the data transfer rate of the second host, and the data transfer rate of respective one or more intervening packet processing platforms located between the first and second hosts; and

transmitting data packets from the first host to the second host at a data transfer rate that is less than or equal to the throttle value.

17. (Original) The method of Claim 16, wherein setting the maximum data transfer rate of the first host to the throttle value is accomplished by Application Programming Interface (API) calls from an application executing on the first host to a sockets layer of the first host.

18. (Original) The method of Claim 16, wherein transmitting data packets from the first host to the second host at a data transfer rate that is less than or equal to the throttle value is accomplished by use of a User Datagram Protocol (UDP) transport layer and an Internet Protocol network layer.

19. (Currently Amended) A method comprising:

receiving, during a communication start-up process, a throttle value that is less than or equal to the ~~lesser~~ least of a data transfer rate of a source device, a data transfer rate of a destination device, and a data transfer rate of respective one or more intervening packet processing platforms located between the source and destination devices;

setting the maximum data transfer rate of the source device to the throttle value; and

transmitting data packets from the source device to the destination device at a data transfer rate that is less than or equal to the throttle value.

20. (Previously Presented) The method of Claim 19, wherein setting the maximum data transfer rate of the source device to the throttle value is accomplished by Application Programming Interface (API) calls from an application executing on the source device to a sockets layer of the source device.

21. (Previously Presented) The method of Claim 19, wherein transmitting data packets from the source device to the destination device at a data transfer rate that is less than or equal to the throttle value is accomplished by use of a User Datagram Protocol (UDP) transport layer and an Internet Protocol network layer.

22. (Currently Amended) An apparatus comprising:

a processor configured to:

obtain a data transfer rate of a first host, ~~and~~ a data transfer rate of a second host, and a data transfer rate of a network through which data is transferred from the first host to the second host; and

Appl. No.: 10/758,854
Amdt. dated 12/12/2008
Reply to Office action of October 7, 2008

set a throttle value for transmission of data from the first host to the second host to a value that is less than or equal to the ~~lesser~~least of the data transfer rate of the first host, ~~and the data transfer rate of the second host, and the data transfer rate of the network, respectively,~~ wherein the throttle value is set during a communication start-up process.

23-25. (Canceled).

26. (Previously Presented) The apparatus of Claim 22, wherein the processor is further configured to:

set the maximum data transfer rate of the first host to the throttle value.

27. (Previously Presented) The apparatus of Claim 26, wherein in order to set the maximum data transfer rate of the first host to the throttle value, the processor is further configured to:

establish one or more Application Programming Interface (API) calls from an application layer of the first host to a socket layer of the first host.

28. (Canceled).